



Protect what matters most.



www.PipeBurstPro.com

FloMeter Spec Sheet

FloMeter Overview

Fully integrated with ionleaks.com, FloMeter empowers monitoring and control over how much water is being used in a user specified period of time. NSF61 & Low Lead approved Bronze body.

Specs:

Size	5/8 x 3/4 inch
Typical Operating Range	100% +/- 1.5%
Low Flow (95% - 101%)	1-20 gpm
Max Continuous Operating Flow	1/8 gpm
Max Operating Capacity	15 gpm
Pressure Loss at Max Flow	20 gpm
Max Operating Temperature	7.0 psi
Max Operating Pressure	122°F
Starting Flow	150 psi
Extreme High Flow (intermittent)	1/32 gpm
	28 gpm

Meets or exceeds latest revision of AWWA C700 Performance Standards



FM025: 5/8 x 3/4 inch

Physical Characteristics: inches

Meter length (Screw Ends)	7 1/2
Meter Casing Spuds	
Nominal Thread Size	1
Couplings (Tailpieces)	
Length	2 1/2
Length with Couplings	12 1/2
Nominal Thread Size	3/4
Weight	4.6 lbs
Height	4 3/4"

Meets or exceeds latest revision of AWWA C700 Dimensional Standards

*Encoder top will be different than what is pictured

FloMeter Features

- User friendly interface through ionleaks.com
- Control maximum water usage for a specified period of time.
- Set time protocols for a minute, hour, day, week, or month.
- Automatically low flow, shut off or notify water when gallon/time parameters are exceeded.

©2018 GreenField Direct, LLC rev.1.1.29.18



800.246.LEAK (5325)
info@greenfielddirect.com

